



ENTECH OIL

PRODUCT DATA

ENTECH OUTLAW SERIES TRANSMISSION FLUID MV-ATF

PACKAGE SIZES:

1 QUART BOTTLE	500502-Q
6/1 QUART BOTTLES	500502-6Q
2/1 GALLON BOTTLES	500502-2G
2/2.5 GALLON BOTTLES	500502-5G
55 GALLON DRUM	500502-D



Description:

- ENTECH Outlaw Series Synthetic Multi-Vehicle ATF is a premium quality fluid designed for modern domestic and imported vehicles with automatic transmissions.
- ENTECH Outlaw Series Synthetic Multi-Vehicle ATF is formulated with synthetic base stocks and premium additives that maintain viscosity and have excellent sheer stability and oxidation resistance.
- ENTECH Outlaw Series Synthetic Multi-Vehicle ATF protects transmissions against corrosion, sludge-deposits, while preventing degradation of seals, clutches, and bearings.
- ENTECH Outlaw Series Synthetic Multi-Vehicle ATF Manages friction to provide smooth and consistent shifting in domestic and imported automatic transmissions.
- ENTECH Outlaw Series Synthetic Multi-Vehicle ATF is for use in foreign and domestic vehicles where multi-vehicle ATF is recommended.

Physical Properties (Typical):

Entech Synthetic Multi-Vehicle ATF		
API Gravity	ASTM D-1298	35.2
Viscosity, cSt @ 40 °C	ASTM D-445	30.6
Viscosity, cSt @ 100 °C	ASTM D-445	6
Viscosity Index	ASTM D-2270	147
Flash Point °C (°F)	ASTM D-92	217 (423)
Pour Point, °C (°F)	ASTM D-97	-54 (-65)