



ENTECH OIL

PRODUCT DATA

ENTECH OUTLAW SERIES Synthetic Gear Oil

PACKAGE SIZES:

1 QUART BOTTLE

6/1 QUART BOTTLES

2/1 GALLON BOTTLES

2/2.5 GALLON BOTTLES

55 GALLON DRUM

50040X-1Q

50040X-6Q

50040X-2G

50040X-5G

50040X-D



Description:

- ENTECH Synthetic Gear Oils (SGO) are full synthetic high-performance gear lubricant, that exceeds GL-5 Limited Slip specifications.
- ENTECH SGO delivers outstanding power transfer performance and meets the following rigorous specifications: GL-4, GL-5 LS, SAE J2360, MT-1, Ford WDS-M2C200-C, MACK GO-J & J Plus, Scania STO 1:0, MAN 342 Long Life Oil.
- ENTECH SGO contains proprietary additives optimized to provide formulation stability against corrosion, viscosity loss, wear, and thermal degradation associated with extreme conditions.

Physical Properties (Typical):

| Typical Specification | 75W-90 | 80W-140 |
|-------------------------|-----------|-----------|
| Specific Gravity | 0.8590 | 0.8700 |
| Pour Point, °C (°F) | -29 (-20) | -26 (-15) |
| Flash Point, °C | > 170 | > 170 |
| Viscosity, cSt @ 40 °C | 121 | 311 |
| Viscosity, cSt @ 100 °C | 16.0 | 31.3 |
| Odor | Mild | Mild |