



ENTECH OIL

PRODUCT DATA

ENTECH XP-ATF FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID

PACKAGE SIZES:

| | |
|----------------------|-----------|
| 1 QUART BOTTLE | 500501-Q |
| 6/1 QUART BOTTLES | 500501-6Q |
| 2/1 GALLON BOTTLES | 500501-2G |
| 2/2.5 GALLON BOTTLES | 500501-5G |
| 55 GALLON DRUM | 500501-D |



Description:

- Entech PRO Series XP-ATF is full synthetic Automatic Transmission Fluid.
- Entech PRO Series XP-ATF is specifically formulated for use in automatic racing transmissions.
- Entech PRO Series XP-ATF is engineered for extreme torque, high-horsepower and high temperatures.
- ENTECH PRO Series XP-ATF reduces wear, provides lower operating temperatures, faster lockups and smoother shifts.

Physical Properties (Typical):

| Entech Synthetic XP ATF | | |
|-------------------------|-------------|-------|
| API Gravity | ASTM D-1298 | 0.880 |
| Viscosity, cSt @ 40 °C | ASTM D-445 | 37.8 |
| Viscosity, cSt @ 100 °C | ASTM D-445 | 7.7 |
| Viscosity Index | ASTM D-2270 | 178.8 |
| Flash Point °C (°F) | ASTM D-92 | > 218 |