



ENTECH OIL

PRODUCT DATA

ENTECH OUTLAW SERIES 2 STROKE ENGINE OIL

PACKAGE SIZES:

6/1 QUART BOTTLES

500608-6Q

1 GALLON BOTTLE

500608-1G

2/1 GALLON BOTTLES

500608-2G



2T UNIVERSAL ENGINE OIL 500608

Description:

- Entech 2-Cycle (2T) Engine Oil is an ashless multi-purpose 2-Cycle oil. It is a clean burning blend of polyolester, polybutene and synthetic base stocks for high-revving, two-cycle, air or water- cooled, pre-mix engines.
- Suited for gasoline 2-cycle engines either as a premix or oil injection system with fuel/oil ratios from 11:1 to 100:1.
- Low smoke formulation that meets or exceeds API TC, NMMA TC-W3®, ISO-E-GD and JASO- FC standards and all OEM requirements.
- Provides excellent performance in lawn mowers, chain saws, string trimmers, outboard engines, jet skis, motorcycles, snow blowers, Go-karts, and ATVs.

Physical Properties (Typical):

Entech 2-Cycle Engine Oil	
API Gravity	30.8
Pour Point, °C	-42
Flash Point °F	226
Viscosity, cSt @ 100° C	8.5
Color	Green

Mixing Ratio	16:1	24:1	32:1	40:1	50:1
Gallons of Gasoline	Ounces of 2-Cycle Oil				
1	8	5.5	4	3.2	2.5
2	16	10.5	8	6.5	5
3	24	16	12	9.5	7.5
4	32	21.5	16	13	10
5	40	26.5	20	16	13