



ENTECH OIL

PRODUCT DATA

ENTECH OUTLAW SERIES MOTORCYCLE ENGINE OIL

PACKAGE SIZES:
6/1 QUART BOTTLES 500600-6Q
1 GALLON BOTTLE 500600-1G
2/1 GALLON BOTTLES 500600-2G



4T PAO MOTORCYCLE ENGINE OIL 500600
V-TWIN MOTORCYCLE ENGINE OIL 500606
V-TWIN MOTORCYCLE ENGINE OIL 500607

Description:

- Outlaw Motorcycle oils are formulated for high-performance street and racing motorcycle applications.
- Outlaw Motorcycle oils are the highest quality PAO synthetic base oils with an ultra-premium additive package.
- Outlaw Motorcycle oils increase horsepower and torque while lowering operating temperatures.
- Outlaw Motorcycle oils are wet clutch and catalytic converter safe and provide smooth clutch operation.
- Outlaw Motorcycle oils meet and/or exceed 4T, API SL, SJ, SG, SN/JASO MB, API SN/JASO MA2 (T903:2016).

Physical Properties (Typical):

Typical Specifications:

SAE Grade	10W-30	10W-40	10W-50	20W-50	20W-60
Viscosity @ 40°C	62.4	86.4	125	168	171
Viscosity @ 100°C	11	14.5	18	20.4	25.2
Viscosity Index	170	175	160	141.8	181.2
Flash Point (PMCC), °C	> 170	> 170	> 170	> 170	> 170
Density, Lb./gal @ 60°F	7.2	7.22	7.27	7.37	7.37